

Product Name	21.5" Open Frame Capacitive Touch Monitor
Model No. / EAN No.	FT215TMCAPOFHB0B / 6920734022120

IP Rating
IP65 Front / IP40 Back

LCD Panel	
Screen diagonal (Inch/cm)	21.5/54.69
Display active screen size (cm)	47.70 × 26.80
Aspect ratio	16:9
Physical resolution	1920 × 1080
Maximum showable resolution	1920 × 1200
Colours displayed	16.7M
Brightness (cd/m²)	1000
Contrast	1000:1
Typical reaction time Tr/Tf (ms)	7/7
Visual Angle horizontal/vertical (°)	178/178
Backlight / Backlight Lifetime (hours)	LED / 100,000



External Connectors	
Video	1x HDMI 1.3 (incl. HDCP)
	1x DVI-D
	1x VGA
Audio	1x PC-Audio
Touch Connector	1x USB
Connectors	1x Serial
	1x 12V DC-In

Touch Panel	
Touch Technology	Projected Capacitive 10-point Multitouch
Touch Panel Drivers	Windows; Linux; Mac; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Surface Treatment	Anti glare (chemical etching)

Operation / Mechanical	
Operating Temperature (° C)	-10 ~ +60
Humidity Range (RH)	10% - 90%
Net weight (kg)	5.00
Gross weight (kg)	7.30 (incl. cartonage)
Housing material (open frame)	Aluminum
Housing (mm) L × W × H	527.9 × 328.0 × 51.1
Cut-out required (mm) L × H	506.0 × 314.0
Amount of clamps required	8
(optional) Tape length required (mm)	1660.0 (2 × 516.0 + 2 × 314.0)
(optional) Amount of glue required (ml)	8.30
Mounting	VES A 100

Power	
Power Supply	100-240V ACDC active switching; 12V DC-Out
Working Power (V)	12
Power Consumption (W)	28
Stand-By Consumption (W)	<1

Included in the Delivery	
Power Supply (see Power section)	
Short Installation Manual	
HDMI Cable	
USB Cable	



General Tolerance ISO 2768c

Corporate Headquarters

faytech AG

Bischhäuser Aue 10
37213 Witzenhausen
Germany

support@faytech.com
contact@faytech.com
www.faytech.com

China: +86 755 8958 0612
Germany: +49 5542 30374 10
USA: +1 646 205 3214
India: +91 11 49707436
Japan: +070 4127 5167